



PHMSA R&D Working Group #5 Methane Mitigation- Construction and Operations


December 2021

Chris Moore, Ph.D
Program Manager

OTD Mission and Goals

Mission

- Identify, select, fund, and oversee research projects resulting in innovative solutions and the improved safety, reliability, and operational efficiency of natural gas systems



Goals

- Enhance safety
- Enable operational excellence
- Minimize environmental impact
- Practice good science

Operations Technology Development (OTD) Overview

Established 2003

Stand-alone, not-for-profit, member-controlled company where gas utilities work together to develop technology solutions to common issues


- Annual membership dues are calculated based on number of customer meters
- New projects selected by members based on needs
- Each member votes their own dollars to specific projects
- All members have access to all project information

28 Members

\$12M
annual dues





























\$150-\$750k
member/yr

\$0.50
meter/yr





OTD Members

Serving 50 million gas consumers in the U.S., Canada and France

Methane Measurement, Mitigation, and Operations







Methane Emission Quantification

- Accepted methodologies for quantifying emissions are limited
- Especially for buried assets




PH MSA R&D Forum-Working Group #5-December 2021







Purging Gas Pipes into Service without Venting

- Develop an alternative vacuum focused method to purge gas pipes into service with no or minimal gas vented
- Vacuum, “pump-downs,” to remove air that entered when out of service
- Pure system gas introduced eliminating emissions from purging
- In Phase 2 now - moving to commercial ready system



Straightforward Retrofit Concept to Existing Wellhead Arrangement


Current Systems:



Implementation of this system reduces:

- NG losses by more than 97%
- GHG emissions by greater than 99.9%

Retrofit:




• Based on Allen, et. al., Measurement of methane emissions at natural gas production sites in the United States, PNAS, Vol. 110, No. 44, pp 17768-17773

** Using GHG intensification factor of 28

*** Assumes 2.27 cycles per day per controller, per conversation with D. Sevier SWN



Design and Placement of Compact Service Regulators

- Research on "vent limiting" gas service regulators that will provide gas utilities with more options for outside placement.
- Vent limiting regulators produce less natural gas emissions as compared to traditional internal relief valve regulators.
- Comparative testing includes:
 - Measurement of Emissions
 - Measurement of Concentration



Design of a Comprehensive Natural Gas Smart Safety Shutoff System

- Consists of 4 main components
 1. Smart Sensors: RMD, Fire, Flood, e.g.
 2. Smart Shutoff Valve
 3. Communication Network
 4. User Interface Software
- RMD detects low LEL methane levels starting at 10%
- Communicates LEL levels to the gas utility to dispatch an employee to investigate.
- Smart valve shuts off the gas flow to the building to prevent gas levels from reaching the explosive limit.



Needs and Challenges

- Verifiable and accepted quantification methodologies
- Discussion on wider use of flaring in transmission and distribution
- Other procedural updates
- Addressing PIPES Act emissions issues while being safety compliant
- Low-cost pressure monitoring sensors



Questions

